



Wasseraustritt umlaufend

* 2=verzinkt, 3=Chromnickelstahl

Rohrdurchmesser- und Rundheitstoleranz nach DIN EN 10296-1
 Längen und Winkelmaße – DIN ISO 2768-1 – Toleranzklasse V

Rohr	Ø 80	Ø 100	Ø 120	Ø 140	Ø 150	Ø 175	Ø 200	Ø 224
Artikel-Nr.	1208*805	1210*805	1212*805	1214*805	1215*805	1217*805	1220*805	1222*805
Ø d	76	99	119	135	149	174	199	219
Ø D	92	115	135	151	165	190	215	235
Ø A	230	230	260	310	310	360	460	515
B	110	110	125	130	130	160	200	235
C	188	152	169	222	200	237	322	368
L	360	325	355	415	390	460	620	695
S	2	2	2	2	2	2	2	2
Gewicht in kg	3,2	3,4	5,2	6,4	6,2	9,5	12,5	16,5
Rohr	Ø 250	Ø 280	Ø 300	Ø 315	Ø	Ø	Ø	Ø
Artikel-Nr.	1225*805	1228*805	1230*805	1231*805	-	-	-	-
Ø d	249	276	299	311	-	-	-	-
Ø D	265	292	315	327	-	-	-	-
Ø A	515	570	575	590	-	-	-	-
B	235	245	255	255	-	-	-	-
C	322	330	335	335	-	-	-	-
L	650	655	680	690	-	-	-	-
S	2	2	2	2	-	-	-	-
Gewicht in kg	15,5	17,50	18,5	19,00	-	-	-	-

Deflektorhauben
 Ø80-Ø315

04/20

Maßblatt-Nr.

6/23

Rev.

0